

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in application:

1. (Currently amended) A device for supporting a display on a rear view mirror of a vehicle, said rear view mirror having a post for connecting said mirror to said vehicle, said device comprising:

a hook configured to receive said post for hanging said device;

a pocket connected to said hook, said pocket configured for receiving said display and comprising a first planar wall and a second planar wall both extending laterally between a first outermost edge and a second outermost edge, said first planar wall also extending further in an upwards direction than said second planar wall;

wherein said first planar wall having a first portion, said first portion comprising the difference in length between said first planar wall and said second planar wall, said first portion extending laterally between the first outermost edge and the second outermost edge wherein said first planar wall and said second planar wall are connected together through a single fold and wherein said first planar wall is formed co-planar with said hook, and said second

planar wall is substantially parallel with said first planar wall and wherein said first planar wall is connected to said second planar wall only along said single fold such that said first planar wall is separable from said second planar wall along a length of said second planar wall away from said fold and the first planar wall and the second planar wall are biased toward each other to hold the display in position there between; and

wherein said hook is formed of a rigid material such that said display is supported in said pocket without deforming said hook wherein said hook is formed as an open loop and wherein said device is formed of a thermoplastic material and is of one piece unitary construction and wherein said device is formed of a transparent material such that said display can be viewed through said pocket.

2. (Cancelled)

3. (Cancelled)

4. (Cancelled)

5. (Cancelled)

6. (Cancelled)

7. (Cancelled)

8. (Cancelled)

9. (Cancelled)

10. (Cancelled)

11. (Currently amended) A device for supporting a display,
said device comprising:

a hook configured to receive a support for hanging said
device, wherein said hook is formed as an open loop;

a pocket integrally connected to said hook, said pocket
configured for receiving said display, said pocket
comprising a unitary member forming a first planar wall and
a second planar wall, said first planar wall and said second
planar wall being connected only at a fold along a bottom
portion of said device and both extending laterally between
a first outermost edge and a second outermost edge
throughout their entire lengths, said first and second
outermost edges being parallel, and said first planar wall

extending further in an upwards direction than said second planar wall;

wherein the first planar wall comprises a first portion, said first portion comprising the difference in length between said first planar wall and said second planar wall, said first portion also extending laterally between the first outermost edge and the second outermost edge and wherein said first planar wall is formed co-planar with said hook, and said second planar wall is substantially parallel with said first planar wall and wherein said fold provides a hinge such that said first planar wall can be separated from said second planar wall for inserting said display between said first planar wall and said second planar wall and the second planar wall are biased toward each other to hold the display in position there between; and

wherein said pocket is formed of a transparent material such that said display may be viewed through said pocket and wherein said device is constructed of a substantially rigid plastic material.

12. (Cancelled)

13. (Cancelled)

14. (Cancelled)

15. (Cancelled)

16. (Cancelled)

17. (Currently amended) A method for forming a display support, said method comprising the steps of:

a) obtaining a single piece of transparent material having sufficient rigidity to support the weight of said display support and the weight of a display without substantial deflection;

b) forming a hook in a first end of said transparent material; [and]

c) forming a fold in said transparent material to define a pocket having a first planar wall co-planar with said hook, and a second planar wall substantially parallel with said first planar wall, said first planar wall extending further in an upwards direction than said second planar wall, said first planar wall and second planar wall having a same width in the lateral direction throughout; and

(d) inserting said display in said pocket and holding the display in said pocket with a compressive force created

by said first planar wall and said second planar wall
imposed by said fold.

18. (Cancelled)

19. (Cancelled)

20. (Currently amended) A device for supporting a display on a rear view mirror of a vehicle, said rear view mirror having a post for connecting said mirror to said vehicle, said device comprising:

a hook configured to receive said post for hanging said device, said hook formed as an open loop; and

a pocket for receiving said display, said pocket integrally connected to said hook and comprising a unitary member forming a first planar wall and a second planar wall, said first planar wall and said second planar wall being connected only at a U-shaped fold along a bottom portion of said device and said first and second planar walls being of equal width throughout;

wherein said hook is formed of a substantially rigid material such that said display is supported in said pocket without deforming said hook;

wherein said first planar wall is formed co-planar with said hook, and said second planar wall is substantially parallel with said first planar wall;

wherein a length of said second planar wall is less than a length of said first planar wall to provide a space between an end of said second planar wall and said hook; [and]

wherein said device is formed of a transparent material such that said display can be viewed through said first planar wall and said second planar wall; and

wherein the hook comprises a shank, the shank being about one inch wide and at least one inch long, having a first and second edge, the first edge of the shank being contiguous with a first edge of the first planar wall, the first edge of the planar wall residing in a near vertical position when the device is hung from a rear view mirror, and the second edge of the shank being contiguous with a top edge of the first planar wall, the top edge of the first planar wall residing in a near horizontal position when the device is hung from a rear view mirror and wherein the hook comprises a shank having a first and second edge, the first edge of the shank being contiguous with a first edge of the first planar wall, the first edge of the planar wall residing in a near vertical position when the device is hung

from a rear view mirror, and the second edge of the shank being contiguous with a top edge of the first planar wall, the top edge of the first planar wall residing in a near horizontal position when the device is hung from a rear view mirror.

21. (Cancelled)

22. (Cancelled)

23. (Cancelled)

24. (Cancelled)

25. (Cancelled)

26. (Cancelled)

27. (Cancelled)

28. (Cancelled)